

## 2009 Truck Derby Rules

### General Rules:

1. All derby participants, and pit crew will be expected to behave in a sportsman like manner. Any person determined by an event staff member, derby official, or law enforcement to be disruptive will be ejected without refund from the property along with the party they are with.
2. No one will be allowed in the derby if found to be under the influence of drugs or alcohol.
3. All drivers must be at least 16 years of age. Any driver under the age of 18 must have a parent or guardian sign a waiver and release form for minors. NO EXCEPTIONS!!!!

### Car Prep rules:

1. ½ ton pickups only. **NO 4 WHEEL DRIVES. 2- WHEEL DRIVES ONLY.** Numbers must be on both sides of the truck.
2. Remove all glass, lights, lenses, mirrors, and hardware. Remove all body trim, hubcaps, and exterior ornaments.
3. Remove original fuel tank and mount tank in the bed of the truck, use a 6-gallon boat tank or fuel cell if possible. The fuel container must be covered.
4. Remove trailer hitch and all mounting hardware, Remove all interior upholstery, plastic, carpet, and trim. Must have a fire extinguisher present at inspection.

### Doors and Door Reinforcements:

1. Doors must be welded or chained.
2. Driver's door may be reinforced on the inside with a maximum of 1-inch thick plating. No more than 3 inches past the door seams, and no more than 24 inches wide.

### Hoods

1. Truck hoods are mandatory.
2. Mandatory 2 holes in hood on each side of carburetor for engine fires. Header holes will work.
3. Hoods must be fastened in 6 places: no wire or chains from hood to bumper.

### Tailgates and Truck beds

1. Tailgate can be welded from top to bottom on both sides. No other reinforcements allowed.
2. Factory stock bed.
3. Factory bolts in bed, can use 4-inch washer on top of bed bolt.

## Battery

1. Battery must be moved to passenger side floorboard or passenger side seat and secured. Must have cover and **ONLY ONE BATTERY IS ALLOWED.**

## Electrical Switches

1. If you use an electrical fuel pump, the switch must be placed in the dash area and Labeled FUEL PUMP and the on and off must be labeled.

## Fuel system

1. Fuel tank must be mounted in truck bed, centered behind the cab, and secured properly. It must be an official approved tank, an 8"x8" hole must be cut in front panel of bed and back of cab for fuel lines to pass thru. No sharp edges.

## Cooling System

1. Cooling system must remain stock and no movement of the radiator.

## Bumpers

1. Standard truck bumpers only!! No push guards. No trailer hitches.
2. Bumpers can be welded to the frame.

## Tires and Rims

1. Any stock rim that fits the bolt pattern as long as it is not a split or two piece rim.
2. Valve stem protectors are **NOT allowed.**
3. Maximum tire height of 31 inches, and **NO LIFT KITS ARE ALLOWED.**